

# PRODUCT INFORMATION

## Passenger Car Motor Oils GLOBAL



### 5W-30 SP Global Plus

#### Motor Oil for Petrol Engines

#### DESCRIPTION

**REKTOL 5W-30 SP Global Plus** is an engine oil specially designed for highly charged petrol engines, which offers special protection against LSPI (Low Speed Pre-Ignition = premature fuel ignition) and timing chain protection. The special viscosity level also enables high fuel savings. According to the manufacturer's instructions, it can also be used in vehicles with turbo petrol hybrid engines. This high-performance product may only be used in modern engines that explicitly release engine oils of the viscosity class SAE 5W-30.

#### THIS PRODUCT IS RECOMMENDED BY REKTOL IF THE FOLLOWING FILLING REQUIREMENTS ARE REQUIRED:

SAE 5W-30

API SP (RC), API SN (RC)

ILSAC GF-6A, GF-5

Ford WSS-M2C945/946/947

Ford WSS-M2C960/961/962

GM DX1-Gen 2, Gen 3; GM 6094 M

Chrysler MS-6395

Fiat 9.55535-CR1

Toyota; Lexus; Honda; Nissan; Hyundai; KIA;

Mazda; Mitsubishi; Daihatsu; Isuzu; Subaru;

Suzuki

#### TYPICAL CHARACTERISTICS

Properties	Testing according	Data	Unit
Density at 15°C	DIN 51757	0,854	g/ml
CCS -30 °C	ASTM-D 5293	5200	cP
Pourpoint	DIN ISO 3016	< -35	°C
Viscosity at 40 °C	DIN 51562	72	mm <sup>2</sup> /sec
Viscosity at 100 °C	DIN 51562	11,8	mm <sup>2</sup> /sec
Viskosity Index	DIN ISO 2909	160	

# PRODUCT INFORMATION

## Passenger Car Motor Oils GLOBAL



### AVAILABLE PACKAGING



Item-number: 106052811 106052814 106052816 106052820



Item-number: 106052830 106052836

The information in this product data sheet is based on over 127 years of experience of company Rektol GmbH & Co. KG. Our professional competence in the development and manufacturing of lubricants are based on the current state-of-the-art. Universally valid statements regarding the function of our lubricants are not possible, because the lubricant performance can be influenced by a series of factors. As a result the lubricant filling process, the exact purpose of use, the general operating conditions, the system degree of wear and the system contamination etc. must be taken into account in particular in engines, machinery and equipment. The data given in this product data sheet represents general, non-binding guideline values. No warranty expressed or implied is given concerning the properties. We recommend to consult our application engineer regarding the application conditions and requirements before the REKTOL lubricant is used. The user should test the functional suitability of our lubricants in the intended application and use the product with the corresponding care and responsibility according to the manufacturer's specifications. Our products undergo continuous improvements. We therefore reserve the right to change our product program, the products and their manufacturing processes as well as all details at any time and without warning. Please note: Our products may not be used in aircraft and spacecraft or parts thereof.