

# PRODUCT INFORMATION

## 4T Motoroil



### 5W-40 Street Bike

#### 4T Motorcycle Motoroil

#### DESCRIPTION

**5W-40 Street Bike** is a HC-synthetic motor oil with extreme high temperature stability. Formulated for air- and water-cooled motorcycles with high speed fourstroke engines, equipped with a common oil reservoir of engine, gear box and wet clutch system. Guarantees maximum performance, without any negative influence on the stability of the engine.

#### THIS PRODUCT IS RECOMMENDED BY REKTOL IF THE FOLLOWING FILLING REQUIREMENTS ARE REQUIRED:

SAE 5W-40  
API SN

JASO MA2 (T903:2011)

#### ADVANTAGES

- high operating safety
- excellent wear protection through outstanding lubrication
- outstanding corrosion protection
- very good oxidation stability
- low evaporation loss
- suitable for dry and oil bath clutch systems (please observe operational regulations!)

#### TYPICAL CHARACTERISTICS

##### Properties

	Test according to	Data	Unit
Density at 15°C	DIN 51757	0,855	g/ml
CCS -30 °C	ASTM-D 5293	5900	cP
Pourpoint	DIN ISO 3016	< -35	°C
Viscosity at 40 °C	DIN 51562	80	mm <sup>2</sup> /sec
Viscosity at 100 °C	DIN 51562	14	mm <sup>2</sup> /sec
Viscosity Index	DIN ISO 2909	180	

# PRODUCT INFORMATION


## 4T Motoroil



### Available Packaging



Item-number: 107054011 107054014 107054016 107054020



Item-number: 107054030 107054036

The information in this product data sheet is based on over 127 years of experience of company Rektol GmbH & Co. KG. Our professional competence in the development and manufacturing of lubricants are based on the current state-of-the-art. Universally valid statements regarding the function of our lubricants are not possible, because the lubricant performance can be influenced by a series of factors. As a result the lubricant filling process, the exact purpose of use, the general operating conditions, the system degree of wear and the system contamination etc. must be taken into account in particular in engines, machinery and equipment. The data given in this product data sheet represents general, non-binding guideline values. No warranty expressed or implied is given concerning the properties. We recommend to consult our application engineer regarding the application conditions and requirements before the REKTOL lubricant is used. The user should test the functional suitability of our lubricants in the intended application and use the product with the corresponding care and responsibility according to the manufacturer's specifications. Our products undergo continuous improvements. We therefore reserve the right to change our product program, the products and their manufacturing processes as well as all details at any time and without warning. Please note: Our products may not be used in aircraft and spacecraft or parts thereof..